

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
14 October 2004 (14.10.2004)

PCT

(10) International Publication Number  
**WO 2004/087544 A1**

(51) International Patent Classification<sup>7</sup>: **B65G 39/12**

(21) International Application Number:  
PCT/NL2004/000192

(22) International Filing Date: 18 March 2004 (18.03.2004)

(25) Filing Language: Dutch

(26) Publication Language: English

(30) Priority Data:  
1023050 31 March 2003 (31.03.2003) NL

(71) Applicant (for all designated States except US): **TECH-  
NISCHE UNIVERSITEIT DELFT** [NL/NL]; Ju-  
lianalaan 134, NL-2628 BL Delft (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **LODEWIJKS,  
Gabriel** [NL/NL]; Hoofdkanaal OZ 102, NL-7881 CP  
Emmer-Compascuum (NL). **DRENTH, Karel, Frederik**  
[NL/NL]; Waterlelie 48, NL-2804 PW Gouda (NL).


(74) Agent: **VAN BREDA, Jacques et al.**; Octrooibureau Los  
En Stigter B.V., Weteringschans 96, NL-1017 XS Amster-  
dam (NL).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-  
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,  
GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,  
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,  
ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: SUPPORTING ORGAN FOR AN AXIALLY MOVING BODY



(57) Abstract: A supporting body (1) for an axially moving body such as a conveyor belt, a cable or a stepless escalator, comprising a roller (3) rotatable about a shaft (2) for the support of the body and at least a first support (4) in which the shaft of the roller is mounted for carrying the roller, wherein a second support is provided, wherein the first support and the second support (5) are designed to cooperate in carrying the roller, wherein the second support is fixedly mounted and the first support can, in the moving body's direction of movement, be fixedly coupled with the second support, while in a plane perpendicular to this direction of movement, the first support is rotatable about a pivoting point located on a contact surface shared by the roller and the body to be supported by the roller.

WO 2004/087544 A1

Express Mail Label  
EV336982065US



**Published:**

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

3/10/05

JCO9 Rec'd PCT/PTO 29 SEP 2005

10/551328

WO 2004/087544

PCT/NL2004/000192

**SUPPORTING BODY FOR AN AXIALLY MOVING BODY SUCH  
AS A CONVEYOR BELT, A CABLE OR A STEPLESS  
ESCALATOR**

The invention relates to a supporting body for an axially moving body such as a conveyor belt, a cable or a stepless escalator, comprising a roller rotatable about a shaft for the support of the body and at least a first  
5 support in which the shaft of the roller is mounted for carrying the roller.

Such a supporting organ is known from practice and, as already mentioned, is used with conveyor belts, cables and stepless escalators. Conveyor belts of the kind referred to  
10 may be in use, for example, as travellers at airports or elsewhere, or as conveyor belts for freight. Supermarket checkout systems also employ conveyor belts using support organs of the kind to which the invention relates.

A problem with these applications is that the shaft  
15 of such rollers that support but are not driven, is fixed in relation to the surroundings. As a consequence, there is not always an optimal contact surface between the roller and the body, e.g. the conveyor belt supported by the roller, so that slip may occur as well as excessive wear to belt and roller.

20 The object of the invention is to find a solution to this problem.

To this end the support organ according to the invention is characterised in that a second support is provided, wherein the first support and the second support  
25 are designed to cooperate in carrying the roller, wherein the second support is fixedly mounted and the first support can, in the moving body's direction of movement, be fixedly coupled with the second support, while in a plane perpendicular to this direction of movement, the first  
30 support is rotatable about a pivoting point located on a contact surface shared by the roller and the body to be supported by the roller.

In a further aspect, the supporting organ according to the invention may be advantageously realised such that the  
35 first support and the second support possess intermating slots and pins, wherein the slots have a curve, which is

determined for each slot individually by an imaginary centre and a radius relating to said centre of said slot, such that the centres of all the slots located in the same vertical plane coincide, forming the pivoting point of the first  
5 support. This solution is very elegant, because in this construction the load on the roller from the body to be supported brings about an interplay of forces, which causes the first support to assume a position in which the roller provides optimal support for the body.

10 In a preferred embodiment of the invention, the supporting organ is characterised in that there are curved slots, one or more of which are located above a rotational axis of the roller and one or more of which are located below the rotational axis of the roller, and in that the radii of  
15 said slots possess a common central point located on the bearing surface of the top side of the roller.

Hereinafter the invention will be further elucidated by way of the drawing of a non-limiting exemplary embodiment of the supporting organs according to the invention.

20 The drawing shows in:

- Figure 1 to Figure 3 a series of steps for mounting the supporting organ according to the invention;

- Figure 4 the supporting organ according to the invention in the mounted condition without load; and

25 - Figures 5 and 6, the supporting member according to the invention when loaded.

Similar parts in the figures carry identical reference numbers.

Referring first to Figure 3, the same shows a  
30 supporting organ 1 according to the invention. This supporting organ 1 comprises a roller 3 rotatable about an axis 2 for the support of a body (not shown). This body may be a conveyor belt or a cable or a stepless escalator or another such body. The direction of conveyance of the body is  
35 perpendicular to the plane of the drawing, that is to say the roller 3 also rotates in the direction of conveyance of the body to be supported.

The supporting organ 1 further comprises a first

support 4; this is clearly shown in the Figures 1 and 2. The shaft 2 of the roller 3 is mounted in this first support 4 so that the first support 4 can carry the roller 3.

The first support 4 cooperates with a second support 5, which as a rule is mounted on solid ground so as to render it fixed.

The first support 4 can be coupled with the second support 5 in such a manner that the first support 4 is fixed also, but will exhibit this condition only in the moving body's direction of conveyance, that is to say in the direction perpendicular to the plane of the drawing. In the plane of the drawing, i.e. in the plane perpendicular to the body's direction of conveyance, the first support is mounted to be rotatable about a pivoting point 6 located on a contact surface shared by the roller 3 and the body to be supported by the roller 3.

As clearly shown in the Figures 1 to 3, the first support 4 and the second support 5 are embodied with intermating slots 6 and pins 7. The slots 6 have a curve, which is determined for each slot individually by an imaginary centre 6 and a radius relating to said centre 6 of said slot, such that the centres of all the slots 6 in the same vertical plane coincide and form the pivoting point 6 of the first support 4.

The Figures further clearly show that the curved slots 6 are distributed such that one or several of them are located above the rotational axis of the roller 3 and also one or several slots 6 are located below the rotational axis of the roller 3.

Figures 1 to 3 demonstrate that mounting the supporting organ 1 according to the invention may be extremely simple. Figure 1 shows that the assembly of roller 3 and first support 4 are first moved downward in the direction of arrow A such as to insert a pin 7 of the first support 4 into a slot 6 of the second support 5.

Next, Figure 2 shows that the downward movement in the direction of arrow A can be continued whereby the upper pin of the first support 4 finds the lowest point of the

upper slot 6 of the second support 5, and the lower pin 7 of the first support 4 can be inserted into the second support 6, which is the slot 6 located at the underside of said second support 5.

5           Next, Figure 3 shows the supporting organ 1 in the mounted condition, which corresponds to the unloaded position of the supporting organ 1 as shown in Figure 4. This Figure 4 also shows a conveyor belt 8 supported by the roller 3.

          Figures 5 shows a greatly exaggerated situation  
10 arising when the load exerted by belt 8 is increased. As a result of the interplay of forces then occurring, the assembly of roller 3 and first support 4 rotates about the fixed point of rotation 6 in the direction of arrow B, as shown in Figure 6. The two pins 7 that are mounted on the  
15 first support 4 then move upwards into the slots 6 of the second support 5, thereby finding a new point of equilibrium, where the roller provides optimal support for the belt 8.

          Although the inventors believe that the above given exemplary embodiment presents an optimal form of the manner  
20 in which the invention may be applied, the invention is not limited to this specific exemplary embodiment. In the context of this patent application, the elucidated exemplary embodiment serves exclusively as explanation for the appended claims, while the claims must not be deemed to necessarily be  
25 limited to said given exemplary embodiment. Modifications fulfilling the essence of the invention as established by said claims, possibly supplemented by the specification and the drawings and/or the grant file, are explicitly considered to fall within the protective scope of the claims.

CLAIMS

1. A supporting body for an axially moving body such as a conveyor belt, a cable or a stepless escalator, comprising a roller rotatable about a shaft for the support of the body and at least a first support in which the shaft of the roller is mounted for carrying the roller, **characterised** in that a second support is provided, wherein the first support and the second support are designed to cooperate in carrying the roller, wherein the second support is fixedly mounted and the first support can, in the moving body's direction of movement, be fixedly coupled with the second support, while in a plane perpendicular to this direction of movement, the first support is rotatable about a pivoting point located on a contact surface shared by the roller and the body to be supported by the roller.
2. A supporting body according to claim 1, **characterised** in that first support and the second support possess intermating slots and pins, wherein the slots have a curve, which is determined for each slot individually by an imaginary centre and a radius relating to said centre of said slot, such that the centres of all the slots located in the same vertical plane coincide, forming the pivoting point of the first support.
3. A supporting body according to claim 2, **characterised** in that there are curved slots, one or more of which are located above a rotational axis of the roller and one or more of which are located below the rotational axis of the roller, and in that the radii of said slots possess a common central point located on the bearing surface of the top side of the roller.






FIG. 1

FIG. 2








FIG. 5




FIG. 6

# INTERNATIONAL SEARCH REPORT

Application No  
PCT/NL2004/000192

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 B65G39/12

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B65G F16B F16C F16M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB 2 241 558 A (MURPHY JAMES) 4 September 1991 (1991-09-04) page 10, line 20 - page 11, line 17; figures	1
A	US 2002/060139 A1 (SCHIESSER RICARDO N ET AL) 23 May 2002 (2002-05-23) abstract; claims; figures	1
A	US 4 408 835 A (DEPREZ MICHEL ET AL) 11 October 1983 (1983-10-11) abstract; figures	1
A	DE 41 09 374 C (RITTAL-WERK RUDOLF LOH GMBH) 10 September 1992 (1992-09-10) abstract; figures	1,2

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the International filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the International search

7 July 2004

Date of mailing of the International search report

16/07/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3018

Authorized officer

Schneider, M

# INTERNATIONAL SEARCH REPORT

Application No  
PCT/NL2004/000192

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
GB 2241558	A	04-09-1991	IE	892077 A1	02-01-1991
US 2002060139	A1	23-05-2002	US	6367617 B1	09-04-2002
			AU	1025301 A	23-04-2001
			BR	0014739 A	11-06-2002
			CA	2387475 A1	19-04-2001
			WO	0127004 A1	19-04-2001
			EP	1222125 A1	17-07-2002
			JP	2003517406 T	27-05-2003
US 4408835	A	11-10-1983	FR	2497371 A1	02-07-1982
			DE	3170058 D1	23-05-1985
			EP	0055662 A1	07-07-1982
DE 4109374	C	10-09-1992	DE	4109374 C1	10-09-1992
			FR	2674296 A1	25-09-1992
			GB	2254106 A ,B	30-09-1992